

What is claimed is:

1. A clamp-like device, comprising:
  - 5 (a) a frame;
  - (b) at least two plungers arranged at an angle movably connected with said frame; and
  - 10 (c) double-sided stretch releasing adhesive attached to at least one of said frame and said plungers.
2. A device as defined in claim 1, wherein said stretch releasing adhesive is attached to said frame.
- 15 3. A device as defined in claim 1, wherein said stretch releasing adhesive is attached to said plungers.
4. A device as defined in claim 1, wherein said frame includes an angle section  
20 comprising a pair of connecting portions arranged at an angle, each said connecting portion containing at least one opening.
5. A device as defined in claim 4, wherein each opening is threaded, and further wherein each plunger is externally threaded and is rotatably arranged within an associated  
25 opening.
6. A device as defined in claim 4, wherein said frame further includes a leg portion extending perpendicularly from the end of each connecting portion, and a foot portion arranged on the end of each leg portion.

30

7. A device as defined in claim 6, wherein stretch releasing adhesive for attaching said frame to a surface is provided on each foot portion.
8. A device as defined in claim 4, wherein said frame further includes a pair of parallel leg portions extending from the same connecting portion.
9. A device as defined in claim 1, wherein each said plunger includes a head adapted to receive stretch releasing adhesive.
10. A device as defined in claim 9, wherein each said plunger includes a handle to facilitate manual actuation of the associated plunger.